

CFFDRS Index Thresholds

Class	LOW	MOD	HIGH	VHIGH	EXT	Interpretation
Max Temp (T°)	<50°	50° to 59.9°	60° to 69.9°	70° to 79.9°	80°+	Fire intensity and crown fire potential
Min Relative Humidity (RH%)	51% to 100%	41% to 50%	31% to 40%	21% to 30%	<20%	Fine fuel moisture and ignition potential
Fine Fuel Moisture Code (FFMC)	0 to 79.9	80 to 85.9	86 to 88.9	89 to 91.9	92+	Below 74, little chance of ignition or surface fire spread with an open flame. Active spread in light fuels at 80. Ignition potential high at 90 and extreme fire behavior expected at 92.
Duff Moisture Code (DMC)	0 to 39.9	40 to 59.9	60 to 79.9	80 to 99.9	100+	Duff layer not involved below 20. Influence of duff on surface fire noticeably increases at 40. Extreme fire behavior becomes possible above 60.
Drought Code (DC)	0 to 149.9	150 to 349.9	350 to 399.9	400 to 449.9	450+	Minimal significant ground fire below 300.
Initial Spread Index (ISI)	0 to 1.9	2 to 4.9	5 to 7.9	8 to 10.9	11+	Expected spread potential. Used in fire behavior predictions.
Build-up Index (BUI)	0 to 39.9	40 to 59.9	60 to 89.9	90 to 109.9	110+	Fuel availability and flammability. Seasonal severity. Used in Fire Behavior Predictions.
Fire Weather Index (FWI)	0 to 8.9	9 to 17.9	18 to 27.9	28 to 34.9	35+	Fire intensity and extreme fire potential.
Daily Severity Rating (DSR)	NA	NA	NA	NA	NA	A transformation of the FWI that emphasizes its higher values. Can be cumulated through the season to represent overall conditions.